

Technical Data Sheet

ProtecRSS Pre-Cut Cricket



ProtecRSS Pre-cut Cricket is a combination of pre-engineered tapered and flat rigid mineral wool fiber insulation manufactured from basalt rock and steel slag, having a melting point of approximately 2150°F (1177°C), with a bitumen saturated and lightly sanded surface. The pre-engineered panels make up the various Starter Packs and Filler Packs required in easily and efficiently assembling crickets of any length. An environmentally friendly product, ProtecRSS Pre-cut Cricket is CFC and HCFC free.

Applications **ProtecRSS Pre-cut Cricket** is intended for cold applied, torched or hot asphalt modified bitumen or built-up roofing membrane systems in commercial and industrial roof applications to elevate low areas and allow for proper drainage. It can be installed with hot or cold adhesives, or mechanically fastened.

Standard Dimensions 1/4" (2%) Slope, diamond shaped 3:1 length to width ratio, up to 100' (30.5 m) or greater.
1/2" (4%) Slope, diamond shaped 3:1 length to width ratio, up to 100' (30.5 m) or greater.
Custom crickets available upon request.

Properties Actual density - ASTM C612-0911 lb/ft³ (176 kg/m³)
Dimensional stability - ASTM C356..... Linear Shrinkage 0.01% @ 350°F (177°C)
Moisture resistance - ASTM C209..... Water Absorption <1.0%

Features

- Tapered down to 0"
- Fire resistant
- Made from recycled material
- Excellent moisture resistance
- Excellent dimensional stability
- Will not rot or deteriorate

Compliance CAN 2-51.31-M84 and ASTM C726 (Thermal Insulation - Mineral Fiberboard)

Limitations Do not expose **ProtecRSS Pre-cut Cricket** by ModulR TS to weather during shipment, storage or installation. At completion of day's work, seal all exposed edges. It is not intended for use as a structural roof deck. To avoid damage from construction traffic and material transportation install adequate protective boardwalks over installed roofing materials to enable passage of people and products not limited to the roofing project.

ModulR TS Inc. reserves the right to change the above specifications without prior notice.